according to the OSHA Hazard Communication Standard



Bovilis MH Single Shot RTU / MH + IBR Formulation

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 5.2 09/28/2024 10876233-00013 Date of first issue: 10/24/2022

SECTION 1. IDENTIFICATION

Product name : Bovilis MH Single Shot RTU / MH + IBR Formulation

Other means of identification : Coopers Bovilis MH Single-Shot RTU READY-TO-USE MH

VACCINE FOR CATTLE (92022)

COOPERS BOVILIS MH+IBR BOVINE RESPIRATORY

DISEASE (BRD) VACCINE (64608)

Bovilis MH+IBR (A011518)

COOPERS BOVILIS MH MANNHEIMIA HAEMOLYTICA

VACCINE FOR CATTLE (55767)

Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc Address : 126 E. Lincoln Avenue

Rahway, New Jersey U.S.A. 07065

Telephone : 908-740-4000 Emergency telephone : 1-908-423-6000

E-mail address : EHSDATASTEWARD@merck.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization : Category 1

Carcinogenicity : Category 1B

GHS label elements

Hazard pictograms





Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.

H350 May cause cancer.

Precautionary Statements : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P261 Avoid breathing mist or vapors.

P272 Contaminated work clothing must not be allowed out of

the workplace.

according to the OSHA Hazard Communication Standard



Bovilis MH Single Shot RTU / MH + IBR Formulation

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 5.2 09/28/2024 10876233-00013 Date of first issue: 10/24/2022

P280 Wear protective gloves, protective clothing, eye protection

and face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P308 + P313 IF exposed or concerned: Get medical attention. P333 + P313 If skin irritation or rash occurs: Get medical atten-

tion.

P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste

disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Antigen	Not Assigned	>= 50 - <= 54
White mineral oil (petroleum)	8042-47-5	9.5
Glycerine	56-81-5	1
Formaldehyde	50-00-0	0.3

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty

of water.

Remove contaminated clothing and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse. Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.

Get medical attention.

Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

In case of eye contact

May cause an allergic skin reaction.

May cause cancer.

according to the OSHA Hazard Communication Standard



Bovilis MH Single Shot RTU / MH + IBR Formulation

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 10876233-00013 Date of first issue: 10/24/2022 5.2 09/28/2024

delayed

Protection of first-aiders First Aid responders should pay attention to self-protection,

> and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Treat symptomatically and supportively. Notes to physician

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media Water spray

> Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod- :

ucts

Carbon oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment:

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Avoid release to the environment. **Environmental precautions**

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up Soak up with inert absorbent material.

For large spills, provide diking or other appropriate

containment to keep material from spreading. If diked material

can be pumped, store recovered material in appropriate

container.

according to the OSHA Hazard Communication Standard



Bovilis MH Single Shot RTU / MH + IBR Formulation

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 5.2 09/28/2024 10876233-00013 Date of first issue: 10/24/2022

Clean up remaining materials from spill with suitable

absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust

ventilation.

Advice on safe handling : Do not get on skin or clothing.

Avoid breathing mist or vapors.

Do not swallow.

Avoid contact with eyes.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure

assessment

Keep container tightly closed.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Store locked up. Keep tightly closed.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

Self-reactive substances and mixtures

Organic peroxides

Explosives Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
White mineral oil (petroleum)	8042-47-5	TWA (Mist)	5 mg/m³	OSHA Z-1
		TWA (Inhal-	5 mg/m³	ACGIH
		able particu-		
		late matter)		
		TWA (Mist)	5 mg/m³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL
Formaldehyde	50-00-0	TWA	0.1 ppm	ACGIH
		STEL	0.3 ppm	ACGIH

according to the OSHA Hazard Communication Standard



Bovilis MH Single Shot RTU / MH + IBR Formulation

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 5.2 09/28/2024 10876233-00013 Date of first issue: 10/24/2022

TWA	0.016 ppm	NIOSH REL
С	0.1 ppm	NIOSH REL
PEL	0.75 ppm	OSHA CARC
STEL	2 ppm	OSHA CARC
TWA	0.016 ppm (Formaldehyde)	NIOSH REL
С	0.1 ppm (Formaldehyde)	NIOSH REL

Engineering measures : Use appropriate engineering controls and manufacturing

technologies to control airborne concentrations (e.g., drip-

less quick connections).

All engineering controls should be implemented by facility design and operated in accordance with GMP principles to

protect products, workers, and the environment.

Laboratory operations do not require special containment.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are

unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided

by air purifying respirators against exposure to any

hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other

circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Material : Chemical-resistant gloves

Eye protection : Wear safety glasses with side shields or goggles.

If the work environment or activity involves dusty conditions,

mists or aerosols, wear the appropriate goggles.

Wear a faceshield or other full face protection if there is a potential for direct contact to the face with dusts, mists, or

aerosols.

Skin and body protection

Hygiene measures

Work uniform or laboratory coat.

If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the

working place.

When using do not eat, drink or smoke.

Contaminated work clothing should not be allowed out of the

workplace.

Wash contaminated clothing before re-use.

The effective operation of a facility should include review of engineering controls, proper personal protective equipment, appropriate degowning and decontamination procedures, industrial hygiene monitoring, medical surveillance and the

use of administrative controls.

according to the OSHA Hazard Communication Standard



Bovilis MH Single Shot RTU / MH + IBR Formulation

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 5.2 09/28/2024 10876233-00013 Date of first issue: 10/24/2022

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : suspension

Color : white to off-white

Odor : odorless

Odor Threshold : No data available

pH : 6.0 - 8.0

Melting point/freezing point : 32 °F / 0 °C

Initial boiling point and boiling

range

212 °F / 100 °C (1000 hPa)

Flash point : No data available

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapor pressure : 2.37 kPa (68 °F / 20 °C)

Relative vapor density : No data available

Relative density : 1

Density : No data available

Solubility(ies)

Water solubility : soluble

Partition coefficient: n-

octanol/water

: Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : No data available

Explosive properties : Not explosive

according to the OSHA Hazard Communication Standard



Bovilis MH Single Shot RTU / MH + IBR Formulation

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 Date of first issue: 10/24/2022 5.2 09/28/2024 10876233-00013

Oxidizing properties The substance or mixture is not classified as oxidizing.

Molecular weight No data available

Particle characteristics

Particle size Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity Not classified as a reactivity hazard. Chemical stability Stable under normal conditions. Can react with strong oxidizing agents.

Possibility of hazardous reac-

tions

Conditions to avoid None known. Incompatible materials Oxidizing agents

Hazardous decomposition No hazardous decomposition products are known.

products

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity Acute toxicity estimate: > 20000 ppm

Exposure time: 4 h Test atmosphere: gas Method: Calculation method

Acute toxicity estimate: > 5,000 mg/kg Acute dermal toxicity

Method: Calculation method

Components:

White mineral oil (petroleum):

Acute oral toxicity LD50 (Rat): > 5,000 mg/kg

LC50 (Rat): > 5 mg/l Acute inhalation toxicity

Exposure time: 4 h

Test atmosphere: dust/mist

according to the OSHA Hazard Communication Standard



Bovilis MH Single Shot RTU / MH + IBR Formulation

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 5.2 09/28/2024 10876233-00013 Date of first issue: 10/24/2022

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Glycerine:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Guinea pig): > 5,000 mg/kg

Formaldehyde:

Acute oral toxicity : Acute toxicity estimate: 100 mg/kg

Method: Expert judgment

Remarks: Based on national or regional regulation.

Acute inhalation toxicity : Acute toxicity estimate (Rat): 100 ppm

Exposure time: 4 h
Test atmosphere: gas
Method: Expert judgment

Acute dermal toxicity : LD50 (Rabbit): 270 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

White mineral oil (petroleum):

Species : Rabbit

Result : No skin irritation

Glycerine:

Species : Rabbit

Result : No skin irritation

Formaldehyde:

Result : Corrosive after 3 minutes to 1 hour of exposure

Remarks : Based on national or regional regulation.

Serious eye damage/eye irritation

Not classified based on available information.

Components:

White mineral oil (petroleum):

Species : Rabbit

Result : No eye irritation

according to the OSHA Hazard Communication Standard



Bovilis MH Single Shot RTU / MH + IBR Formulation

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 5.2 09/28/2024 10876233-00013 Date of first issue: 10/24/2022

Glycerine:

Species : Rabbit

Result : No eye irritation

Formaldehyde:

Result : Irreversible effects on the eye Remarks : Based on skin corrosivity.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:

White mineral oil (petroleum):

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Formaldehyde:

Test Type : Human repeat insult patch test (HRIPT)

Routes of exposure : Skin contact Species : Humans Result : positive

Assessment : Probability or evidence of high skin sensitization rate in

humans

Germ cell mutagenicity

Not classified based on available information.

Components:

White mineral oil (petroleum):

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

according to the OSHA Hazard Communication Standard



Bovilis MH Single Shot RTU / MH + IBR Formulation

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 5.2 09/28/2024 10876233-00013 Date of first issue: 10/24/2022

Glycerine:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Test Type: DNA damage and repair, unscheduled DNA syn-

thesis in mammalian cells (in vitro)

Result: negative

Formaldehyde:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: positive

Test Type: In vitro mammalian cell gene mutation test

Result: positive

Test Type: Chromosome aberration test in vitro

Result: positive

Genotoxicity in vivo : Test Type: In vivo mammalian alkaline comet assay

Species: Mouse

Application Route: Inhalation

Result: positive

Germ cell mutagenicity -

Assessment

Positive result(s) from in vivo mammalian somatic cell muta-

genicity tests.

Carcinogenicity

May cause cancer.

Components:

White mineral oil (petroleum):

Species : Rat
Application Route : Ingestion
Exposure time : 24 Months
Result : negative

Glycerine:

Species : Rat
Application Route : Ingestion
Exposure time : 2 Years
Result : negative

according to the OSHA Hazard Communication Standard



Bovilis MH Single Shot RTU / MH + IBR Formulation

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 5.2 09/28/2024 10876233-00013 Date of first issue: 10/24/2022

Formaldehyde:

Species : Rat

Application Route : inhalation (gas)
Exposure time : 28 Months
Result : positive

Carcinogenicity - Assess- : Sufficient evidence of carcinogenicity in animal experiments

ment

IARC Group 1: Carcinogenic to humans

Formaldehyde 50-00-0

OSHA OSHA specifically regulated carcinogen

Formaldehyde 50-00-0

NTP Known to be human carcinogen

Formaldehyde 50-00-0

Reproductive toxicity

Not classified based on available information.

Components:

White mineral oil (petroleum):

Effects on fertility : Test Type: One-generation reproduction toxicity study

Species: Rat

Application Route: Skin contact

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion

Result: negative

Glycerine:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion

Result: negative

Formaldehyde:

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: inhalation (gas)

Result: negative

according to the OSHA Hazard Communication Standard



Bovilis MH Single Shot RTU / MH + IBR Formulation

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 5.2 09/28/2024 10876233-00013 Date of first issue: 10/24/2022

STOT-single exposure

Not classified based on available information.

Components:

Formaldehyde:

Assessment : May cause respiratory irritation.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

White mineral oil (petroleum):

Species: RatLOAEL: 160 mg/kgApplication Route: IngestionExposure time: 90 Days

Species : Rat LOAEL : >= 1 mg/l

Application Route : inhalation (dust/mist/fume)

Exposure time : 4 Weeks

Method : OECD Test Guideline 412

Glycerine:

 Species
 : Rat

 NOAEL
 : 0.167 mg/l

 LOAEL
 : 0.622 mg/l

Application Route : inhalation (dust/mist/fume)

Exposure time : 13 Weeks

Species : Rat

NOAEL : 8,000 - 10,000 mg/kg

Application Route : Ingestion Exposure time : 2 y

Species : Rabbit
NOAEL : 5,040 mg/kg
Application Route : Skin contact
Exposure time : 45 Weeks

Aspiration toxicity

Not classified based on available information.

according to the OSHA Hazard Communication Standard



Bovilis MH Single Shot RTU / MH + IBR Formulation

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 5.2 09/28/2024 10876233-00013 Date of first issue: 10/24/2022

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

White mineral oil (petroleum):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

NOEC (Pseudokirchneriella subcapitata (green algae)): 100

mg/

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox-

icity)

NOEC (Oncorhynchus mykiss (rainbow trout)): 1,000 mg/l

Exposure time: 28 d

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 1,000 mg/l

Exposure time: 21 d

Glycerine:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 54,000 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 1,955 mg/l

Exposure time: 48 h

Toxicity to microorganisms : NOEC (Pseudomonas putida): > 10,000 mg/l

Exposure time: 16 h Method: DIN 38 412 Part 8

Formaldehyde:

Toxicity to fish : LC50 (Morone saxatilis (striped bass)): 6.7 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia pulex (Water flea)): 5.8 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

ErC50 (Desmodesmus subspicatus (green algae)): 4.89 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

NOEC (Daphnia magna (Water flea)): 1.04 mg/l

Exposure time: 21 d

according to the OSHA Hazard Communication Standard



Bovilis MH Single Shot RTU / MH + IBR Formulation

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 5.2 09/28/2024 10876233-00013 Date of first issue: 10/24/2022

ic toxicity) Method: OECD Test Guideline 211

Toxicity to microorganisms : EC50 (activated sludge): 19 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Persistence and degradability

Components:

White mineral oil (petroleum):

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 31 % Exposure time: 28 d

Glycerine:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 92 % Exposure time: 30 d

Method: OECD Test Guideline 301D

Formaldehyde:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 99 % Exposure time: 28 d

Method: OECD Test Guideline 301A

Bioaccumulative potential

Components:

Glycerine:

Partition coefficient: n-

log Pow: -1.75

octanol/water Formaldehyde:

Partition coefficient: n-

: log Pow: 0.35

octanol/water

Remarks: Calculation

Mobility in soil
No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

according to the OSHA Hazard Communication Standard



Bovilis MH Single Shot RTU / MH + IBR Formulation

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 5.2 09/28/2024 10876233-00013 Date of first issue: 10/24/2022

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

(Formaldehyde)

Class : 9 Packing group : III

Labels : CLASS 9 ERG Code : 171 Marine pollutant : no

Remarks : THE ABOVE INFORMATION ONLY APPLIES TO PACKAGE

SIZES WHERE THE HAZARDOUS SUBSTANCE MEETS

THE REPORTABLE QUANTITY.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Formaldehyde	50-00-0	100	33333

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ Calculated product	
		(lbs)	(lbs)
Formaldehyde	50-00-0	100	33333

according to the OSHA Hazard Communication Standard



Bovilis MH Single Shot RTU / MH + IBR Formulation

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 5.2 09/28/2024 10876233-00013 Date of first issue: 10/24/2022

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Respiratory or skin sensitization

Carcinogenicity

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

Formaldehyde 50-00-0 0.3 %

Thiomersal 54-64-8 0.01 %

US State Regulations

Pennsylvania Right To Know

Antigen Not Assigned Water 7732-18-5
White mineral oil (petroleum) 8042-47-5
Glycerine 56-81-5
Formaldehyde 50-00-0
Thiomersal 54-64-8

California Prop. 65

WARNING: This product can expose you to chemicals including Formaldehyde, which is/are known to the State of California to cause cancer, and

Thiomersal, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

White mineral oil (petroleum) 8042-47-5

California Permissible Exposure Limits for Chemical Contaminants

White mineral oil (petroleum) 8042-47-5 Glycerine 56-81-5

California Regulated Carcinogens

Formaldehyde 50-00-0

The ingredients of this product are reported in the following inventories:

AICS : not determined

DSL : not determined

IECSC : not determined

SECTION 16. OTHER INFORMATION

Further information


according to the OSHA Hazard Communication Standard



Bovilis MH Single Shot RTU / MH + IBR Formulation

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 5.2 09/28/2024 10876233-00013 Date of first issue: 10/24/2022

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

NIOSH REL / C : Ceiling value not be exceeded at any time.

OSHA CARC / PEL : Permissible exposure limit (PEL)

OSHA CARC / STEL : Excursion limit

OSHA Z-1 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemical

according to the OSHA Hazard Communication Standard



Bovilis MH Single Shot RTU / MH + IBR Formulation

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 5.2 09/28/2024 10876233-00013 Date of first issue: 10/24/2022

cals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate: NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 09/28/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8